

AIR CONDITIONING & HEATING SYSTEMS

HORIZONTAL HVAC UNITS FOR SPLIT SYSTEMS



Version		Super K	Kool 2	Falkon
Cooling performance	kW	3.5	4.5	7.7
Heating performance	kW	4.3	6.6	10
Airflow	m ³ /h	440	520	660
Electrical consumption	W	100	180	360
Main dimensions	mm	216 x 368 x 137	261 x 384 x 158	297 x 432 x 167

VERTICAL HVAC UNITS FOR SPLIT SYSTEMS



Version [12 V]		MK1	VK9 HVAC	VK9 HVAC FAI*
Cooling performance	kW	7	8	6.5
Heating performance	kW	7.8	10	7.5
Airflow	m ³ /h	700	670	520
Electrical consumption	W	360	300	300
Main dimensions	mm	159 x 428 x 443	174 x 414 x 335	174 x 414 x 335

*Depending on model

PRE-ASSEMBLED HVAC UNITS - KAB



Version		HVAC 4.3 / 3.5	HVAC 6.6 / 4.5	HVAC 10 / 7.7
Cooling performance	kW	3.5	4.5	7.7
Heating performance	kW*	4.3	6.6	10.0
Airflow	m ³ /h*	440	520	725
Electrical consumption	W	100	180	360
Main dimensions	mm	589 x 380 x 137.5	589 x 380 x 160.5	589 x 380 x 169

*Depending on model

AIR CONDITIONING & HEATING SYSTEMS

PRE-ASSEMBLED HVAC UNITS - HK EVO4 HEAD LINER



Version		HK EVO4 Head Liner
Cooling performance	kW	8.6
Heating performance	kW	9.5
Airflow	m ³ /h*	1300
Electrical consumption	W*	190
Main dimensions	mm	487 x 1000 x 132

*Depending on model

ROOFTOP A/C UNIT - RK9



Version		RK9
Cooling performance	kW	7
Heating performance	kW	8,2
Weight	kg	24
Airflow	m ³ /h*	610
Main dimensions	mm	932 x 580 x 192

*Depending on model

PRESSURIZATION SYSTEMS – POSSIBLE COMBINATION WITH EACH VEHICLE HVAC SYSTEM!

CABIN PRESSURIZATION SYSTEM - K PROTEC



Minimum overpressure	20 Pa
Minimum fresh air flow	30 m ³ /h
Certification	Enables cab certification in accordance with EN 15695 Category 4