

FUEL OPERATED HEATERS FOR CONSTRUCTION MACHINERY

HYDRONIC S3



Version [Diesel, 24 V]		Commercial D5L	Commercial D6L
Heating performance	kW	1.3 to 5.0	1.3 to 5.6
Main dimension	mm	215 x 91 x 180 [With straight connection fittings]	
Weight	kg	2.0	
Fuel consumption	l/h	0.59	0.65
Interfaces		CAN/S+	

HYDRONIC M



Version [Diesel, 24 V]		M8 Biodiesel*	M10	M12
Heating performance	kW	1.5 to 8.0	1.5 to 9.5	1.2 to 12.0
Main dimension	mm	331 x 138 x 221		
Weight	kg	6.2		
Fuel consumption	l/h	0.18 - 0.9	0.18 - 1.2	0.15 - 1.5
Interfaces		LIN		

* 100 % biodiesel compatible in accordance with FAME DIN EN 14214

HYDRONIC L



Version [Diesel, 24 V]		L16	L24	L30	L35
Heating performance	kW	16.0	24.0	30.0	35.0
Main dimension	mm	600 x 230 x 222			
Weight	kg	18.0			
Fuel consumption	l/h	2.00	2.90	3.65	4.20
Interfaces		S+			

FUEL OPERATED HEATERS FOR CONSTRUCTION MACHINERY

AIRTRONIC S3 / M3



Version [Diesel, 24 V]		S3 Commercial	M3 Commercial
Heating performance	kW	0.85 to 2.2	1.05 to 4.0
Main dimension	mm	310 x 115 x 122	376 x 140 x 150
Weight	kg	2.5	4.5
Fuel consumption	l/h	0.12 - 0.27	0.12 - 0.49
Interfaces		CAN/S+	